



# Verti-Mix 70



# 🦈 strautmann

## Verti-Mix 70

# - best mix with up to 7 m<sup>3</sup>


The Verti-Mix 70 complements the Strautmann product portfolio in the field of compact single auger mixers. With a mixing volume of up to 7 m<sup>3</sup>, up to 50 dairy cows can be optimally fed with feeding once a day



Special knife options help you to adapt your Vario<sup>2</sup> mixing auger in stepped flight design even better to your needs:




The **bale knife** is perfectly suitable for cutting bales.



2

perfectly adapted to your specific conditions of use. The adjustable bars at the start of the augerflight and an adjustable cutting edge at the remover lead to all fodder components neatly being picked up.

The Strautmann magnetic system (optional extra) directly mounted on the mixing auger offers optimum health protection for yourhigh-yield cows.



For fodder rations containing e.g. beets or potatoes, the root crop knife ensures better mixing and additional crushing of the ingredients.



Optional "INNODUR" wearing elements significantly extend the service life of the Vario<sup>2</sup> mixing auger in stepped flight design..

Technische Änderungen vorbehalten







## Easy discharge

- Discharge via side doors
- Left and/or right
- Loose and homogeneous fodder swathe
- the eccentric position of the discharge openings ensures optimum fodder discharge.

### Ladder

- · Galvanized for long durability
- For easy addition of feed components

## Operating options

• Direct tractor connection (standard)

For more comfort:

• Bowden cable (option)

• Electrical control set (option)

## Weighing devices

- PTM HL 50
- → Management of 50 recipes from up to 30 components
- EZ 2810
- $\rightarrow$  Adding scale
- → Standard with Bluetooth antenna:
- Free Feed App
- Rations can be saved on smartphone
- Feed report can be sent by e-mail

| Technical data                             | Verti-Mix 70                      |
|--|-----------------------------------|
| Dimensions                                 |                                   |
| Length [m]                                 | 4,20                              |
| Width with one-sided discharge [m]         | 2,06                              |
| Width with two-sided discharge [m]         | 2,16                              |
| Height [m]                                 | 2,12 (2,37 with 250 mm extension) |
| Wall thickness [mm]                        | 6                                 |
| Bottom plate [mm]                          | 15                                |
| Gross vehicle weight                       |                                   |
| Gross vehicle weight basic machine [kg]    | 2.280                             |
| Mixing capacity                            |                                   |
| Mixing capacity [m³]                       | 6                                 |
| Mixing capacity with 250 mm extension [m³] | 7                                 |

Technische Änderungen vorbehalten



www.strautmann.com

B. Strautmann & Söhne GmbH u. Co. KG



Bielefelder Straße 53 D-49196 Bad Laer Tel.: +49(0)5424/802-0 Fax: +49(0)5424/802-76 info@strautmann.com www.strautmann.com