



Block distribution wagon

**BVW**



# Block distribution wagon

## – simple & robust

The Strautmann block distribution wagons are an ideal complement for the efficient procedure of picking-up silage by means of silo block cutters.



**Hydraulic loading shovel**

- Silo blocks are easily tipped onto the transport floor by means of the loading shovel
- Picking-up of bulk material also possible

**Effective beater**

- Equipped with aggressive ripping tines
- Fodder is cleanly milled off the block



**Variable transport floor**

- Transport floor is equipped with wide, hot-dip galvanized transport strips
- Infinitely variable speed adjustment via a Bowden cable from the tractor



**Comfortable fodder discharge**

- Transport into the stable without any losses
- Block is undone in the BVW
- Homogeneous discharge via the crossover conveyor



**Drawbar**

- Either for bottom linkage in the linkage drawbar
- or for top linkage in the tractor's towing hook

**Easy operation**

- All hydraulic functions can be operated via Bowden cables from the tractor
- Infinitely variable speed adjustment via operating handle
- Optional adjustment of discharge conveyor speed via Bowden cable

**Optional weighing device**

- All block distribution wagons can be equipped with a weighing device on request
- e.g. PTM HL 50  
→ Management of 50 recipes from up to 30 components



Technical modifications reserved



# UBVW

– universal, simple and robust



## Easy and safe distribution of whole round bales

- Optional three-armed hydraulic retaining bow
- Holds round bale silage directly at the beaters

## Easy undoing of silo blocks or round bales

- 2 effective beaters
- Power required of 30 kW/40 HP
- Undoing of whole round bales without any problems
- Infinitely variable crossover conveyor homogeneously discharges the material



## Technical data

	BVW	UBVW
<b>Dimensions</b>		
Length [m]	3,80	3,80
Width [m]	2,30	2,30
Height [m]	1,80	2,30
Height with bale compressing rake lifted up [m]	-	2,85
Discharge height cross conveyor [m]	0,52	0,52
<b>Tare weight</b>		
Basic machine [kg]	1.700	2.000
<b>Power requirement</b>		
Power requirement [HP]	30/40	30/40
Required hydraulic power [bar]	170	170
Required hydraulic power [l/min]	30	30
<b>Container dimensions (inside)</b>		
Loading space L x W [m]	1,94 x 1,95	1,94 x 1,95
Tailboard L x W [m]	0,91 x 1,92	0,91 x 1,92
<b>Volume</b>		
Volume [m3]	2,85	2,85