



Manure spreader

CS spreader



Compact and flexible

– The CS spreader



CS spreader models

The CS spreader is the successor model of the BE spreader which has proven itself over decades. The compact CS spreader is particularly suitable for businesses with own machinery and ensures effective discharge of manure. The folding side panels enable a double use as a transport trailer.

- CS 75-95
- Loading capacity of 7.5 – 9.5 m³
- The folding side panels enable a double use as a transport trailer
- Easy operation

Contents

Spreading unit and transport floor	4-5
Superstructure and chassis	6
Operation and technical data	7

Robust design for strong performance

- Spreading unit and transport floor

- + Fine distribution
- + Perfect spreading pattern
- + High throughput rate
- + Ideal for spreading on grassland



4-beater spreading unit

- Four upright spreading beaters for operating widths between 6 - 8 m
- Fan-shaped spreading tines ensure even crushing of the spreading material



Spreading unit gearbox

- Easy maintenance for a high degree of reliability
- Inspection windows at each spreading unit gearbox enable a fast visual check of oil levels



Transport floor

- Reliable feed by one (CS 75) or two (CS 95) transport floor lines
- 10 mm thick round steel chains with a breaking load of 13 t each
- Screwed transport floor strips enable easy exchange in case of damage
- 25 mm thick wooden floor



Transport floor drive

- High-torque feed gearing with hydraulic drive
- Adjustment of feed rate by means of control valve on the drawbar
- Infinitely variable adjustment enables easy and exact adaptation of discharge quantity

Intelligent design for more comfort

– Superstructure and chassis



Side panel and extensions

- 400 mm high extension panels optionally available to increase the loading capacity
- Extension panels can be folded down to reduce the charging height
 - Easy charging even with yard loaders or smaller tractors
- Side panels can be completely folded down
 - Flexible double use as a transport trailer



Chassis

Standard equipment

- Single axle with various tyre options
- Large tyres for little rolling resistance and protection of sward

Optional equipment on CS 95

- Spring-loaded tandem chassis for maximum driving comfort
- Optimum driving behaviour even during road travel



Grouping of lubrication points

- Optional lubricating strip for upper spreading beater bearings
- Easy and convenient maintenance

Everything under control

– Operation



Simple direct connection

- Operation of hydraulic functions via direct tractor connection
- Setting of transport floor speed via flow regulation valve

Technical data

	CS 75 with 520/50 R 17 tyres	CS 95 with 520/50 R 17 tyres
Dimensions		
Length [m]	6.16	6.96
Height [m]	2.84	2.88
Outside wheel width [m]	2.17	2.17
Charging height [m]	1.75	1.79
Dead weight		
Dead weight from [kg]	2,000	2,300
Gross vehicle weight rating		
Gross vehicle weight rating [kg]	5,700	8,000
Power required		
Power required from	25 kW / 35 HP	36 kW / 50 HP
Inside dimensions of superstructure		
Length [m]	3.70	4.60
Width [m]	1.80	1.80
Side panel height [m]	0.50	0.50
Loading capacity		
Loading capacity [m³]	7.5	9.5
Streuwerk		
Spreading unit clearance [m]	1.15	1.15



www.strautmann.com

B. Strautmann & Söhne GmbH u. Co. KG



Bielefelder Straße 53
D-49196 Bad Laer
Phone: +49(0)5424/802-0
Fax: +49(0)5424/802-76
info@strautmann.com
www.strautmann.com