



WTL 31



MCD



BKT AW 708



PL 801

Bezeichnung	Hersteller	Profil	Load index	Breite	Aussen-Ø	max. Tragkraft 25 km/h	max. Tragkraft 40 km/h	max. Luftdruck
				mm	mm	kg	kg	bar
8.15-15 Zwilling	BKT	PL 801	14PR	215	720	2.550	2.270	9,00
10.0/75-15.3	Vredestein	AW	10PR	277	779	1.900	1.600	5,00
10.0/75-15.3	BKT	AW	18 PR	274	760	3.150	2.650	7,10
30x11,5-14.5	Delcora	Delcora GSP	150 A 8	300	710	4.000	3.350	8,00
13.5/75-430.9	Vredestein	AW	14PR	360	960	3.740	3.150	5,50
215/75 R 17.5	Windpower	WTL 31	135J	215	760	2.940	2.500	9,10
235/75 R 17.5	Windpower	WTL 31	141J	245	791	3.678	3.133	9,30
250/70-15	BKT	PT HD	18PR	240	745	3.650	2.700	9,50
305/70 R 19.5	Continental	HDR	148J	306	924	4.253	3.623	8,80
315/80 R 22.5	Windpower	WTL 31	154L	312	1076	5.400	4.600	8,50
400/60-15.5	BKT	TR	149 A6	405	875	3.460	2.725	4,90
400/60-15.5	BKT	AW 708	151 A8	405	875	4.250	3.450	6,20
435/50 R 19.5	De Molen	RIB + m. Querr.	160 J	435	928	6.075	5.175	9,00
455/45 R 22.5	Goodyear	MCD	166J	455	960	7.155	6.095	9,00