



Conveyor belt wagon

Aperion



Infinite perfection

-The Strautmann conveyor belt wagons



Aperion

derived from the Greek „apeiros“ for infinite – infinite like the conveyor on the Strautmann conveyor belt wagon and infinite like the variety of possibilities the Aperion offers!

Contents

Endless conveyor belt	4-7
Superstructure	8-9
Extensions	10-11
Chassis	12-13
cover/ operation	14
Technical data	15

Endless possibilities

- all-season use



The Aperion

The Aperion enables all-season use from spring to winter. Wood chips, chopped silage or grain can be as efficiently transported as rape, root crops or even packaged goods, big bags or pallets – the variety of possibilities is almost infinite!



Infinite – Unique – Effective – the endless conveyor belt



Robust transport conveyor belt

- Continuous conveyor avoids operating errors
- 2100 mm wide and 10 mm thick
- rubber conveyor with fabric reinforcement
- Seals at the side ensure an absolutely tight cargo space

Reliable drive

- Hydraulic conveyor drive via a large-sized gearbox and a rubber-coated roller at the rear
- Front return roller automatically ensures permanent tension
- Retightening possible by means of hand-operated hydraulics

Always clean

- The cleaning brush at the return roller prevents the material from becoming clogged, thus avoiding damage to the conveyor

Optimum support

- Carrying and supporting rollers only 30 cm apart ensure optimum support for the belt and guarantee smooth unloading
- Sealed and maintenance-free ball bearings

Unloading – fast and clean – the superstructure



Complete emptying

- Smooth interior, no residues in the cargo space during discharge
- Sealing of conveyor by means of rubber lips
- Plastic strip prevents sticky loaded materials from remaining on the conveyor



Wide opening tailgate

- Wide opening for discharging without any problems
- Mechanical locking mechanism ensures transport without any losses

Easy dosing

- Standard grain gate
- Easy adjustment of discharge speed of bulk materials

Diverse size options

- The extension concept

Optional extensions of 700 mm in height for increased capacity

Standard hydraulically folding front panel.



Variable due to folding elements

- Lateral folding extensions for a reduced charging height
- Tailgate can also be opened with the extension folded down
- Locking of folded-down extensions at the side panels



Fast & comfortable

- Hydraulically telescoping extensions
- Perfectly suitable for versatile use
- Easy extending and retracting of extensions from the cabin
- Safe guiding in the side panel stanchions



Gentle superstructure

- Side panels made of glass-fibre reinforced plastic sections with robust stanchions for optimum transport
- Thermally insulating surface for transport of delicate materials

Optional beaters

- Mechanically powered via large-sized roller chains
- Perfectly suitable for uniform discharge of e.g. grass silage
- Dosing unit can be quickly removed when not in use



Robust & safe on two chassis



Hydraulic tandem chassis

- Standard equipment on the Aperion 2401
- Optimum driving comfort and driving safety
- Hydraulic axle compensation
- Optimum load distribution to all 4 wheels
- Optional suspension



Hydraulic tridem chassis

- Standard equipment on the Aperion 3401
- Optimum driving comfort and reduced ground pressure due to 6 wheels
- 1st & 3rd axle with mechanic-hydraulic forced steering axle system



Comfortable linkage

- Standard bottom linkage with balltype coupling
- Standard mechanical drawbar suspension
- PU elements cushion impacts and vibrations
- Optional hydraulic drawbar suspension

Well covered

- Covering system for any requirements



Folding mesh cover

- For covering e.g. silage or wood chips
- Hydraulic actuation
- Central overlapping ensures complete covering
- Can be combined with extensions

Technical data

	Aperion 2401 with tyres 710/50 R 26.5	Aperion 3401 with tyres 710/50 R 26.5
Dimensions		
Width [m]	2,55	2,55
Height [m]	3,95	3,95
Length [m]	9,75	11,55
Outside wheel width [m]	2,81	2,81
Dead weight		
Dead weight [kg]	8.200	10.200
Gross vehicle weight rating		
with bottom linkage [kg]	24.000	34.000
Inside dimensions of superstructure		
Length [m]	8,10	9,90
Width [m]	2,34	2,34
Height [m]	1,50	1,50
Height with extension [m]	2,20	2,20
Loading capacity		
Loading capacity [m ³]	28,0	35,0
Loading capacity with extension [m ³]	42,0	52,0

Figures, technical data and weights may change due to technical development and are not binding for delivery.

Operation

- simple and practical



Direct connection

- Standard equipment
- Simple & robust




Electro-hydraulic operation via E-Control

- Intuitively arranged toggle switches for each function
- Infinitely variable adjustment of conveyor speed via potentiometer
- Additional conveyor operation at the rear of the vehicle



Our solutions for your business at a glance:



www.strautmann.com

B. Strautmann & Söhne GmbH u. Co. KG



Bielefelder Straße 53
D-49196 Bad Laer
Tel.: +49(0)5424/802-0
info@strautmann.com
www.strautmann.com